

SPECIFICATIONS

Alignment Specifications

Item	LH	RH	Total/ Split
Front			
Caster	$7.1^{\circ} \pm 0.75^{\circ}$	$7.1^{\circ} \pm 0.75^{\circ}$	$0^{\circ} \pm 0.75^{\circ}$
Camber	$-0.75^{\circ} \pm 0.75^{\circ}$	$-0.75^{\circ} \pm 0.75^{\circ}$	$0^{\circ} \pm 0.75^{\circ}$
Toe (positive value is toe-in, negative value is toe-out)	—	—	$0.10 \pm 0.20^{\circ}$

General Specifications

Item	Specification
Front Ride Height	
Front	$37 \text{ mm} \pm 8 \text{ mm}$ (1.5 in \pm 0.3 in)
Rear Ride Height	
Rear — Convertible	$118 \text{ mm} \pm 8 \text{ mm}$ (4.6 in \pm 0.3 in)

General Specifications (Continued)

Item	Specification
Rear — Coupe	$115 \text{ mm} \pm 8 \text{ mm}$ (4.5 in \pm 0.3 in)
Dogtracking	
Maximum	13 mm (0.5 in)
Clear vision (negative value is counterclockwise)	$0^{\circ} \pm 3^{\circ}$
Ball Joint Deflection	
Lower ball joint	0-0.3 mm (0-0.012 in)

Torque Specifications

Description	Nm	lb-ft
Tie-rod jam nut	55	41
Lower control arm rear inboard cam nut	175	129
Strut-to-wheel spindle cam nut	200	148
Brake line bracket bolt	20	15
Wheel speed sensor bolt	15	11